

U.S.S.N. 10/709,438

2

04630 (LC 0151 PUS)

In the claims:

1. (Currently Amended) A method of operating an active night vision system of a vehicle comprising:  
generating a first oscillating signal;  
generating at least one trigger signal having at least one duty cycle with a cycle start time and a cycle end time;  
synchronizing said cycle end time with a pulse end time of said first oscillating signal; and  
operating a light source of the active night vision system in response to said duty cycle.
2. (Previously Presented) A method as in claim 1 further comprising operating a receiver in response to said at least one duty cycle.
3. (Original) A method as in claim 2 wherein said light source and said receiver are activated at said cycle start time and deactivated at said cycle end time.
4. (Previously Presented) A method as in claim 1 wherein generating at least one trigger signal having at least one duty cycle with a cycle start time and a cycle end time is performed via a controller.
5. (Original) A method as in claim 1 wherein synchronizing said cycle end time with a pulse end time of said first oscillating signal is performed via a controller.
6. (Original) A method as in claim 1 further comprising:  
generating a second oscillating signal in response to said first oscillating signal; and

U.S.S.N. 10/709,438

3

04630 (LC 0151 PUS)

synchronizing said cycle start time with a pulse start time of said second oscillating signal.

7. (Original) A method as in claim 1 further comprising synchronizing said cycle start time with a pulse end time of said first oscillating signal.

8. (Previously Presented) A method as in claim 7 wherein synchronizing said cycle start time with a pulse end time comprises synchronizing a rising edge of said at least one duty cycle with a falling edge of said first oscillating signal.

9. (Previously Presented) A method as in claim 1 wherein synchronizing said cycle end time with a pulse end time comprises synchronizing a first falling edge of said at least one duty cycle with a second falling edge of said first oscillating signal.

10-20. (Canceled)

21. (Currently Amended) A method as in claim 1 further comprising:

generating a second oscillating signal;

generating a pre-trigger signal having a first duty cycle in response to said first oscillating signal and said second oscillating signal;

detecting pulse endings of said first oscillating signal and said second oscillating signal and generating a post-trigger signal having a second duty cycle; and

operating [[a]]said light source in response to said second duty cycle.

22. (Currently Amended) A method as in claim 21 further comprising operating a receiver in response to said second duty cycle.

U.S.S.N. 10/709,438

4

04630 (LC 0151 PUS)

23. [[22.]] (Currently Amended) A method as in claim 21 where said first oscillating signal is associated with horizontal oscillation of a receiver.

24. [[23.]] (Currently Amended) A method as in claim 21 wherein said pre-trigger signal is partially synchronized with said first oscillating signal.

25. [[24.]] (Currently Amended) A method as in claim 21 wherein said post-trigger signal is fully synchronized with said first oscillating signal.

26. [[25.]] (Currently Amended) A method as in claim 21 wherein said second oscillating signal is an approximately 60Hz oscillating signal.

27. [[26.]] (Currently Amended) A method as in claim 1 further comprising:

generating a second oscillating signal;

generating said at least one trigger signal in response to said first oscillating signal and said second oscillating signal; and

counting pulses within said first oscillating signal in relation to said second oscillating signal; and

synchronizing said cycle end time with a second pulse end time of said first oscillating signal.

28. (Previously Presented) A method as in claim 27 comprising synchronizing said cycle start time with a first pulse end time of said first oscillating signal.